


| 3000 Series - ERC Version [50 Hz] |                     | Model        |     |      |    |
|-----------------------------------|---------------------|--------------|-----|------|----|
|                                   |                     | 3055         |     | 3075 |    |
|                                   |                     | L            | H   | L    | H  |
| Working pressure                  | bar                 | 7            | 10  | 7    | 10 |
| Free air delivery (*)             | m <sup>3</sup> /min | 8,5          | 7,5 | 11,5 | 10 |
| Electric Motor                    | kW                  | 55           |     | 75   |    |
| Electric feeding                  | V-n° Ph. -Hz        | 400 / 3 / 50 |     |      |    |
| Enclosure- insulation class       |                     | IP 23 - F    |     |      |    |
| Maximum Oil Carry-Over            | p.p.m.              | ≤ 5          |     |      |    |
| Oil system capacity               | l                   | 37           |     |      |    |
| Nominal Rotational Speed          | r. p. m.            | 1500         |     |      |    |
| Sound pressure level (**)         | db (A)              | 90           |     |      |    |
| Outlet air temperature            | K                   | <7           |     |      |    |

| 3000 Series - ERC Version [60 Hz] |                     | Model        |    |      |     |
|-----------------------------------|---------------------|--------------|----|------|-----|
|                                   |                     | 3055         |    | 3075 |     |
|                                   |                     | LX           | HX | LX   | HX  |
| Working pressure                  | bar                 | 7            | -  | 7    | 10  |
| Free air delivery (*)             | m <sup>3</sup> /min | 9            | -  | 12   | 9,7 |
| Electric Motor                    | kW                  | 55           |    | 75   |     |
| Electric feeding                  | V-n° Ph. -Hz        | 400 / 3 / 60 |    |      |     |
| Enclosure- insulation class       |                     | IP 55 - F    |    |      |     |
| Maximum Oil Carry-Over            | p.p.m.              | ≤ 5          |    |      |     |
| Oil system capacity               | l                   | 37           |    |      |     |
| Nominal Rotational Speed          | r p. m.             | 1800         |    |      |     |
| Sound pressure level (**)         | db (A)              | 92           |    |      |     |
| Outlet air temperature            | K                   | <7           |    |      |     |

(\*) Air Delivery as per ISO 1217:1996, annex "C"

(\*\*) As per PN8NTC2.3; average value measured from a distance of 1 m



| Dimensions (mm) 3000 Series |      |     |      |      |
|-----------------------------|------|-----|------|------|
| MODEL                       | A    | B   | C    | kg   |
| ERC 3055                    | 2320 | 920 | 1220 | 925  |
| ERC 3075                    | 2370 | 920 | 1220 | 1000 |