


4000 Series - AC Version [50 Hz]		Model										
		AC 55			AC 75			AC 55			AC 4110	
		L	H	HH	L	H	HH	L	H	HH	L	H
Working pressure	bar	8	10	13	8	10	13	8	10	13	7	10
Free air delivery (*)	m ³ /min	10,67	9,5	8,37	14,31	12,65	11,17	16,79	14,11	12,48	19,2	15,25
Electric Motor	kW	55			75			90			110	
Electric feeding	V-n° Ph. -Hz	400 / 3 / 50			400 / 3 / 50			400 / 3 / 50			400 / 3 / 50	
Enclosure- insulation class		IP 55 - F			IP 55 - F			IP 55 - F			IP 55 - F	
Maximum Oil Carry-Over	p.p.m.	≤ 3			≤ 3			≤ 3			≤ 3	
Oil system capacity	l	50			50			50			50	
Nominal Rotational Speed	r. p. m.	1500			1500			1500			1500	
Sound pressure level (**)	db (A)	68			68			69			78	
Outlet air temperature	°C	≤31 (20)			≤31 (20)			≤31 (20)			≤31 (20)	

woking pressure: 7,5 bar for 8 bar version - 9,5 bar 10 bar version - 12,5 bar for 13 bar version

(*) Air Delivery as per ISO 1217:1996, annex "C"

(**) As per PN8NTC2.3; average value measured from a distance of 1 m



Dimensions (mm) 4000 Series				
MODELLO	A	B	C	kg
AC 55	2150	1200	1890	1580
AC 75	2150	1200	1890	1610
AC 90	2150	1200	1890	1640
AC 4110	2150	1200	1815	1800